

vivid.

easymount.
SIGN

WIDE FORMAT LAMINATING SYSTEM

Easymount Sign is designed to perform and built to last.



▲ EM-S1600H

KEY FEATURES

- Up to 5m/16ft a minute
- Heat Assist & Cold options available
- 25mm/1" mounting thickness
- Large diameter rollers
- Variable speed control
- Built-in media take-up unit
- Self gripping mandrels
- Magic eye safety feature
- Heated roller
- Single lift mechanism
- Heavy duty construction
- Release liner take-up
- Handy reverse mechanism
- Foot pedal

GREAT FOR USE IN

- Sign makers
- Print finishers

IDEAL WHEN LAMINATING

- Single banners
 - Reel-to-reel laminates
 - Posters, graphics and signs
 - Mounting prints to boards
 - Pop-up displays
 - Applying vinyls, tapes and adhesive films
 - Outdoor signage
- and many more...

Design & Performance

This Easymount® Sign laminator is designed to perform and built to last, with its solid heavy duty construction.

An easy-to-use laminating system with self gripping mandrels and a flip down feed tray.

The Easymount® Sign includes an integral media take-up unit, making the system ideal for single banners or reel-to-reel laminating up to 50m.

The Easymount® Sign is available as a hot or cold option, in both 1.4m and 1.6m widths.

*Heated roller available on EM-S1400H & EM-S1600H models.

INCLUDES

- BUILT-IN MEDIA TAKE-UP UNIT
- SELF GRIPPING MANDRELS
- SINGLE LIFT MECHANISM

Heat Assist

Cold

Specifications	EM-S1400H	EM-S1600H	EM-S1400C	EM-S1600C
Laminating Speed (m/ft/min)	up to 5m/16ft	up to 5m/16ft	up to 5m/16ft	up to 5m/16ft
Max. Width (mm/inches)	1420mm/56"	1620mm/64"	1420mm/56"	1620mm/64"
Mounting Thickness (mm/inches)	25mm/1"	25mm/1"	25mm/1"	25mm/1"
Roller Diameter (mm/inches)	130mm/5"	130mm/5"	130mm/5"	130mm/5"
Laminating Temperature (°C/°F)	45°C/113°F - can be switched off	45°C/113°F - can be switched off	-	-
Pressure Adjustment	Manual	Manual	Manual	Manual
Film Core (mm/inches)	77mm/3"	77mm/3"	77mm/3"	77mm/3"
Power Supply AC (V-Hz)	220/240-50-60	220/240-50-60	220/240-50-60	220/240-50-60
Power Consumption (W)	1000	1200	38	38
Overall Dimensions (mm/inches)	1846x550x1365mm 73x22x54"	2046x550x1365mm 81x22x54"	1846x550x1365mm 73x22x54"	2046x550x1365mm 81x22x54"
Gross Machine Weight (Kg/lbs)	136Kg/300lbs	156Kg/344lbs	136Kg/300lbs	156Kg/344lbs
Gross Stand Weight (Kg/lbs)	25Kg/55lbs	30Kg/66lbs	25Kg/55lbs	30Kg/66lbs
Warranty*	1 year	1 year	1 year	1 year

*For full terms & conditions on parts and labour warranty, visit vivid-online.com/support/warranty_information

Scan with your smartphone to watch the video



/vividlaminating

@vividlaminating

/vividlaminating

Vivid Laminating Technologies Ltd

Matrix House, Norman Court, Ivanhoe Business Park, Ashby de la Zouch, Leicestershire LE65 2UZ England

vivid-online.com

+44 (0)845 1 30 40 50 sales@vivid-online.com

Vivid care about the environment and is an ISO 14001 registered company.